

TECHNICAL DATA SHEET

ULTRASTAB – TBLS (Tri Basic Lead Sulphate)

Coral Petro products manufactures a complete line of Lead Stabilizer which are recognized as a most versatile of all stabilizers said to process rigid PVC Pipes, Fittings & Profiles.

ULTRASTAB –TBLS is excellent stabilizer for rigid and flexible PVC where good heat stability is required. It is also recommended for cable sheathing and cable insulation due to outstanding electrical properties. It shall be used in consumption with DBLS or LS as per the application.

S.NO.	PARAMETER	VALUE
1	Appearance	Fine White Powder
2	Metalic Content %age as PbO	88- 89
3	Specific Gravity	6.3 - 6.8 -
4	Bulk Density , gm/cc	1.2 – 1.5
5	Moisture content % , Max	0.5
6	Mesh Size 100% Pass Through	200 Mesh

APPLICATION:

PVC Compounds, Rigid PVC Pipes & cables, PVC Profiles & Flooring, PVC Footwear, Master Batches

RECOMMENDED DOSAGE: 2.0 - 6.0 PHR

PACKINGS:

The materials shall be packed in 25 Kgs bag. The bags will be properly sealed to ensure prevention of moisture ingress. On each bag our name, grade, batch no., date of Manufacture along with gross weight and net weight will be clearly mentioned.

GUARANTEE:

Each consignment supplied shall be accompanied by a material safety data sheet and a test Certificate certifying the conformity of the material to the purchasers material specification.